

PNOZ X2.9P C 24VDC 3n/o 1n/c

787300



Safety relay (standalone) Inputs: 1-/2-channel wiring without detection of shorts across contacts Outputs: 3 N/O, 1 N/C. Automatic/manual/monitored start UB 24 V DC, width: 22.5 mm, plug-in spring-loaded terminals. Monitoring E-STOP, safety gates.

Technical details

| | |
|--|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Instantaneous E-STOP monitoring;Limit switch;Light beam device mon. Type 2 with t/p;Light beam device mon. Type 2 w/o t/p;Light beam device mon. Type 4;Safety gate monitor |
| Operating modes: | Single-channel;Automatic reset;Dual-channel;Manual reset;Monitored manual reset;without detection of shorts across contacts |
| Product standard: | EN 60947-5-1 |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal style: | Plug-in |
| Terminal type: | Spring-loaded terminal |
| Number of instantaneous safety contacts: | 3 |
| Number of delayed safety contacts: | 0 |
| Number of auxiliary contacts: | 1 |
| Number of semiconductor outputs: | 0 |
| Stop category: | 0 |
| Max. current at DC13 I (6 cycles/min): | 4.0 A |
| Max. current at AC15: | 3.0 A |
| Width dimension: | 22.5 mm |
| Height dimension: | 101.0 mm |

| | |
|----------------------|-------------|
| Depth dimension: | 121.0 mm |
| Gross weight: | 190 g |
| Net weight: | 180 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



374290

PNOZ X Set spring loaded terminals P1+P2